

BG96 NIDD

AT Commands Manual

LTE Module Series

Rev. BG96_NIDD_AT_Commands_Manual_V1.0

Date: 2018-05-25

Status: Released



Our aim is to provide customers with timely and comprehensive service. For any assistance, please contact our company headquarters:

Quectel Wireless Solutions Co., Ltd.

7th Floor, Hongye Building, No.1801 Hongmei Road, Xuhui District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: info@quectel.com

Or our local office. For more information, please visit:

<http://quectel.com/support/sales.htm>

For technical support, or to report documentation errors, please visit:

<http://quectel.com/support/technical.htm>

Or email to: support@quectel.com

GENERAL NOTES

QUECTEL OFFERS THE INFORMATION AS A SERVICE TO ITS CUSTOMERS. THE INFORMATION PROVIDED IS BASED UPON CUSTOMERS' REQUIREMENTS. QUECTEL MAKES EVERY EFFORT TO ENSURE THE QUALITY OF THE INFORMATION IT MAKES AVAILABLE. QUECTEL DOES NOT MAKE ANY WARRANTY AS TO THE INFORMATION CONTAINED HEREIN, AND DOES NOT ACCEPT ANY LIABILITY FOR ANY INJURY, LOSS OR DAMAGE OF ANY KIND INCURRED BY USE OF OR RELIANCE UPON THE INFORMATION. ALL INFORMATION SUPPLIED HEREIN IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

COPYRIGHT

THE INFORMATION CONTAINED HERE IS PROPRIETARY TECHNICAL INFORMATION OF QUECTEL WIRELESS SOLUTIONS CO., LTD. TRANSMITTING, REPRODUCTION, DISSEMINATION AND EDITING OF THIS DOCUMENT AS WELL AS UTILIZATION OF THE CONTENT ARE FORBIDDEN WITHOUT PERMISSION. OFFENDERS WILL BE HELD LIABLE FOR PAYMENT OF DAMAGES. ALL RIGHTS ARE RESERVED IN THE EVENT OF A PATENT GRANT OR REGISTRATION OF A UTILITY MODEL OR DESIGN.

Copyright © Quectel Wireless Solutions Co., Ltd. 2018. All rights reserved.

About the Document

History

Revision	Date	Author	Description
1.0	2018-05-25	Lane HAO	Initial

Contents

About the Document	2
Contents	3
Table Index	4
1 Introduction	5
2 Description of AT Commands	6
2.1. Description of NIDD Related AT Commands	6
2.1.1. AT+QCFGEXT="pdp_type" Modify the Parameters of Specified PDP Context.....	6
2.1.2. AT+QCFGEXT="nipdcfg" Configure Parameters for NIDD Connection	7
2.1.3. AT+QCFGEXT="nipd" Open or Close the NIDD Connection	7
2.1.4. AT+QCFGEXT="nipds" Send MO Non-IP Data	8
2.1.5. AT+QCFGEXT="nipdr" Retrieve MT Non-IP Data	9
2.2. Description of NIDD Related URCS	10
2.2.1. URC of Incoming Data	10
2.2.2. URC of Connection Closed	10
2.3. Example of NIDD Related Configurations	10
3 Summary of <err> Codes	12
4 Appendix A References.....	13

Table Index

TABLE 1: SUMMARY OF <ERR> CODE	12
TABLE 2: RELATED DOCUMENTS	13
TABLE 3: TERMS AND ABBREVIATIONS	13

1 Introduction

The support for NIDD (Non-IP Data Delivery) is introduced from 3GPP Rel. 13 and later releases. Functions for NIDD may be used to handle MO and MT communication with UE, where the data used for the communication is considered unstructured from the EPS standpoint (which we refer to also as Non-IP). NIDD is only applicable for LTE Cat NB1 RAT. Non-IP data calls are supported for both tethered and embedded use cases.

This document mainly introduces how to use the NIDD function of Quectel BG96 module through AT commands.

2 Description of AT Commands

2.1. Description of NIDD Related AT Commands

2.1.1. AT+QCFGEXT="pdp_type" Modify the Parameters of Specified PDP Context

AT+QCFGEXT="pdp_type" Modify the Parameters of Specified PDP Context

Write Command Query the current configuration: AT+QCFGEXT="pdp_type"	Response +QCFGEXT: "pdp_type",<cid>,<type>,<apn> OK
---	---

Write Command Configure the parameters of a specified PDP context: AT+QCFGEXT="pdp_type",<cid>,<type>[,<apn>[,<username>,<password>]]	Response OK
---	-----------------------

Parameter

<cid>	Integer type. PDP context identifier. A numeric parameter which specifies a particular PDP context definition (see AT+CGDCONT command in <i>Quectel_BG96_AT_Commands_Manual</i> for more details). It is currently only valid for <cid> is 1.
<type>	String type. Packet data protocol type. "IP" "PPP" "IPV6" "IPV4V6" "Non-IP"
<apn>	String type. Access point name.
<username>	String type. User name of the selected APN.
<password>	String type. Password of the selected APN.

NOTE

The command will take effect after reboot, or by executing **AT+CFUN=0** and **AT+CFUN=1** consecutively.

2.1.2. AT+QCFGEXT="nipdcfg" Configure Parameters for NIDD Connection

AT+QCFGEXT="nipdcfg" Configure Parameters for NIDD Connection

Write Command Query the current configuration for NIDD connection: AT+QCFGEXT="nipdcfg"	Response +QCFGEXT: "nipdcfg",<type>,<apn> OK
Write Command Configure the parameters for NIDD connection: AT+QCFGEXT="nipdcfg",<type>[,<apn>[,<username>,<password>]]	Response OK

Parameter

<type>	Non-IP outgoing data type. 0 MO Non-IP data type 1 MO Exception Non-IP data type
<apn>	String type. Access point name.
<username>	String type. User name of the selected APN.
<password>	String type. Password of the selected APN.

2.1.3. AT+QCFGEXT="nipd" Open or Close the NIDD Connection

AT+QCFGEXT="nipd" Open or Close the NIDD Connection

Write Command Configure to open or close the NIDD connection: AT+QCFGEXT="nipd",<mode>[,<time out>]	Response OK If <mode> is 1, the following URC is reported after the OK response: +QIND: "nipd","open",<err> If there is an error related to ME functionality, response: +CME ERROR: <err>
--	---

If there is any other error, response:

ERROR

Parameter

<mode>	Integer type. 0 Close the NIDD connection. 1 Open the NIDD connection.
<timeout>	Integer type. The range is 30-90 and the default value is 30. Unit: second.
<err>	Integer type. The error code of the operation. Please refer to Chapter 3 for details.

NOTES

1. NV 73916 should be set as 277 to enable NIDD function.
2. Non-IP data calls are supported for AP embedded and tethered RmNet calls only.
3. Non-IP data calls are not supported for modem embedded calls.

2.1.4. AT+QCFGEXT="nipds" Send MO Non-IP Data

AT+QCFGEXT="nipds" Send MO Non-IP Data

Write Command	Response
Configure the MO Non-IP data to be sent: AT+QCFGEXT="nipds",<mode>,<data>[,<data_length>]	OK
	If there is an error related to ME functionality, response: +CME ERROR: <err>
	If there is any other error, response: ERROR

Parameter

<mode>	Integer type. Data format. 0 ASCII format string. 1 HEX format string.
<data>	String type. The data to be sent.
<data_length>	Integer type. The data length to be sent. The range is 1-100. Unit: byte.
<err>	Integer type. The error code of the operation. Please refer to Chapter 3 for details.

2.1.5. AT+QCFGEXT="nipdr" Retrieve MT Non-IP Data

AT+QCFGEXT="nipdr" Retrieve MT Non-IP Data

<p>Write Command</p> <p>AT+QCFGEXT="nipdr" [<read_length>]</p>	<p>Response</p> <p>If the connection has received data, response: +QCFGEXT: "nipdr",<read_actual_length>,<data></p> <p>OK</p> <p>If there is no data that can be retrieved, response: +QCFGEXT: "nipdr",0</p> <p>OK</p> <p>If there is an error related to ME functionality, response: +CME ERROR: <err></p> <p>If there is any other error, response: ERROR</p>
<p>Write Command</p> <p>When <read_length> is 0, query the retrieved data: AT+QCFGEXT="nipdr",0</p>	<p>Response</p> <p>If the connection has existed, response: +QCFGEXT: "nipdr",<total_receive_length>,<have_read_length>,<unread_length></p> <p>OK</p> <p>If there is an error related to ME functionality, response: +CME ERROR: <err></p> <p>If there is any other error, response: ERROR</p>

Parameter

<read_length>	Integer type. The data length to be retrieved. Unit: byte.
<read_actual_length>	The actual length of retrieved data. Unit: byte.
<data>	String type. Retrieved data.
<total_receive_length>	The total length of received data. Unit: byte.
<have_read_length>	The length of read data. Unit: byte.
<unread_length>	The length of unread data. Unit: byte.
<err>	Integer type. The error code of the operation. Please refer to Chapter 3 for

details.

2.2. Description of NIDD Related URCs

2.2.1. URC of Incoming Data

After receiving MT Non-IP data, the module will report URC as **+QIND: "nipd","recv"** to notify the host. Then host can retrieve data via **AT+QCFGEXT="nipdr"**. Please note that if the buffer is not empty, and the module receives data again, it will not report a new URC until all the received data has been retrieved via **AT+QCFGEXT="nipdr"** from buffer. The size of the buffer is 2048 bytes. If the data received exceeds the buffer size, the subsequent data will be discarded.

URC of Incoming Data

URC Format	Description
+QIND: "nipd","recv"	URC to notify the host incoming data from network. Then the host can retrieve the data through AT+QCFGEXT="nipdr" .

2.2.2. URC of Connection Closed

URC of Connection Closed

URC Format	Description
+QIND: "nipd","close"	URC to notify that the connection has been accidentally closed. If the connection is closed via the AT+QCFGEXT="nipd",0 , this URC will be not reported.

2.3. Example of NIDD Related Configurations

```

AT+QCFGEXT="pdp_type",1,"Non-IP","cmcc" //Modify the parameters of the first PDP context.
OK
AT+CFUN=0
OK
AT+CFUN=1
OK
AT+CEREG?
+CEREG: 0,1

OK
AT+QCFGEXT="nipdcfg",0,"cmcc" //Set the Non-IP data type and APN.

```

```
OK
AT+QCFGEXT="nipdcfg"
+QCFGEXT: "nipdcfg",0,"cmcc"

OK
AT+QCFGEXT="nipd",1,30 //Open NIDD connection.
OK

+QIND: "nipd","open",0
AT+QCFGEXT="nipds",0,"quectel",7 //Send the string "quectel" in ASCII format via NIDD
connection.

OK
AT+QCFGEXT="nipds",1,"6162636465",10 //Send the string "abcde" in hex format via NIDD
connection.

OK

//When there is any incoming data from the network, the following URC will be reported.
+QIND: "nipd","recv"
AT+QCFGEXT="nipdr",0 //Query the received data length.
+QCFGEXT: "nipdr",10,0,10 //There are 10 bytes data that have been received.

OK
AT+QCFGEXT="nipdr",10 //Read 10 bytes of the incoming data.
+QCFGEXT: "nipdr",10,"0123456789"

OK
AT+QCFGEXT="nipdr",0 //Query the received data length.
+QCFGEXT: "nipdr",10,10,0

OK
AT+QCFGEXT="nipd",0 //Close the NIDD connection.
OK
```

3 Summary of <err> Codes

The error code <err> indicates an error related to mobile equipment or network. The details about <err> are described in the following table.

Table 1: Summary of <err> Code

<err>	Meaning
0	Operation successful
651	Invalid input value
652	Send error
653	Network error
654	NIDD Busy
655	Timeout error
656	Connection not open
657	Connection already opened
658	Connection accidentally closed

4 Appendix A References

Table 2: Related Documents

SN	Document Name	Remark
[1]	Quectel_BG96_AT_Commands_Manual	BG96 AT Commands Manual

Table 3: Terms and Abbreviations

Abbreviation	Description
AP	Application Processor
EPS	Evolved Packet System
ME	Mobile Equipment
MO	Mobile Originated
MT	Mobile Terminated
NIDD	Non-IP Data Delivery
NV	Non-volatile
UE	User Equipment