

TCB

GRANT OF EQUIPMENT AUTHORIZATION

TCB

Certification Issued Under the Authority of the **Federal Communications Commission** By:

Telefication B.V. Edisonstraat 12a Zevenaar, NL-6902 PK Netherlands

Date of Grant: 06/13/2018

Application Dated: 06/12/2018

Quectel Wireless Solutions Company Limited 7th Floor, Hongye Building, No.1801 Hongmei Road, Xuhui District Shanghai, 200233 China

Attention: Johnny xiang

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER:

Name of Grantee: **Equipment Class:**

Notes:

M

XMR201605EC25A

Quectel Wireless Solutions Company Limited

PCS Licensed Transmitter

LTE Module

Modular Type:	Single Modular			
Grant Notes	FCC Rule Part	Frequency	Output	Frequency Emission
		Range (MHZ)	Watts	Tolerance Designator
	22H	826.4 - 846.6	0.205	2.5 PM 4M15F9W
	24E	1852.4 - 1907.6		2.5 PM 4M15F9W
	27	1712.4 - 1752.6		2.5 PM 4M15F9W
	27	699.7 - 715.3	0.225	2.5 PM 1M11G7D
	27	699.7 - 715.3	0.192	2.5 PM 1M10W7D
	27	700.5 - 714.5	0.238	2.5 PM 2M75G7D
	27	700.5 - 714.5	0.199	2.5 PM 2M76W7D
	27	701.5 - 713.5	0.237	2.5 PM 4M54G7D
	27	701.5 - 713.5	0.201	2.5 PM 4M54W7D
	27	704.0 - 711.0	0.242	2.5 PM 9M12G7D
	27	704.0 - 711.0	0.206	2.5 PM 9M12W7D
	24E	1850.7 - 1909.3	0.242	2.5 PM 1M10G7D
	24E	1850.7 - 190 <mark>9.3</mark>		2.5 PM 1M10W7D
	24E	1851.5 - <u>1908.5</u>	0.244	2.5 PM 2M76G7D
	24E	1851.5 - <mark>1908.5</mark>	0.199	2.5 PM 2M76W7D
	24E	1852.5 - 1907.5	0.24	2.5 PM 4M54G7D
	24E	1852.5 - 1907.5	0.191	2.5 PM 4M54W7D
	24E	1855.0 - 1905.0	0.244	2.5 PM 9M12G7D
	24E	1855.0 - 1905.0	0.192	2.5 PM 9M12W7D
	24E	1857.5 - 1902.5	0.235	2.5 PM 13M6G7D
	24E	1857.5 - 1902.5	0.19	2.5 PM 13M6W7D
	24E	1860.0 - 1900.0	0.234	2.5 PM 18M6G7D
	24E	1860.0 - 1900.0	0.193	2.5 PM 18M6W7D
	27	1710.7 - 1754.3	0.24	2.5 PM 1M10G7D
	27	1710.7 - 1754.3	0.209	2.5 PM 1M11W7D
	27	1711.5 - 1753.5	0.202	2.5 PM 2M75G7D
	27	1711.5 - 1753.5	0.202	2.5 PM 2M76W7D



27	1712.5 - 1752.5	0.237	2.5 PM	4M52G7D
27	1712.5 - 1752.5	0.201	2.5 PM	4M52W7D
27	1715.0 - 1750.0	0.236	2.5 PM	9M08G7D
27	1715.0 - 1750.0	0.198	2.5 PM	9M08W7D
27	1717.5 - 1747.5	0.236	2.5 PM	13M5G7D
27	1717.5 - 1747.5	0.192	2.5 PM	13M5W7D
27	1720.0 - 1745.0	0.224	2.5 PM	18M5G7D
27	1720.0 - 1745.0	0.2	2.5 PM	18M5W7D

Class II change: The minor circuitry for non-transmitter portions is changed

Single Modular Approval. Output power is conducted. LTE supports 1.4/3/5/10/15/20 MHz BW modes in Band 2 and Band 4, 1.4/3/5/10 MHz BW modes in Band 12. This device is to be used in mobile or fixed applications only. Antenna gain including cable loss must not exceed 9.6 dBi of frequency band 699-716 MHz, 6 dBi of frequency band 1710-1755 MHz, 9 dBi of frequency band 1850-1910 MHz, 10.92 dBi of frequency band 824-849 MHz, for the purpose of satisfying the requirements of CFR 47 §2.1043 and §2.1091. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operated in conjunction with any antenna or transmitter. The final product operating with this transmitter must include operating instructions and antenna installation instructions, for end-users and installers to satisfy RF exposure compliance requirements. Compliance of this device in all final product configurations is the responsibility of the Grantee. Installation of this device into specific final products may require the submission of a Class II permissive change application containing data pertinent to RF Exposure, spurious emissions, ERP/EIRP, and host/module authentication, or new application if appropriate. This device contains functions that are not operational in U.S Territories. This filling is only applicable for US operations.

Certificate No.: 182180704/AA/00

Gürhan Vural Product Assessor GAN